

C9500 HS SANURAI

HIGH SPEED ELECTRIC WINCH



The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Complete with heavy duty integrated wireless remote.



STANDARD ACCESSORIES

- Armortek Synthetic rope 9.5mm X 30m
- 3m Remote Handset
- Aluminium Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook
- ** Fairlead does not attach direct to the winch **

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

SPECIFICATION

RATED LINE PULL: 9500lbs (4500kg) **MOTOR:** 12v: 6.5hp / 4.5kw

GEARING: 110:1

BRAKING ACTION: Automatic in the drum

DRUM SIZE Dia x L: 63 x 224mm CABLE Dia x L: 9.5mm x 30m MOUNTING PATTERN: 254 x 114.3mm DIMENSIONS: 577 x 160 x 215mm

TECHNICAL PERFORMANCE

Layer of	Line pull		
wire rope	lbs (kg)		
1	9500 (4309)		
2	7706 (3495)		
3	6482 (2940)		
4	5400 (2400)		

Line pull	Line speed		Amp draw	
lbs (kg)	ft/min	m/min	12v	24v
0	65	19.8	80	45
4000 (1818)	12.5	3.8	300	175
6000 (2722)	11.81	3.6	400	230
9500 (4309)	8.86	1.9	530	335