



GET THE ORIGINAL



		9,500 Lb features	12,000 Lb features	15,500 Lb features	17,500 Lb features
Waterproof		IP67 Rating	IP67 Rating	IP67 Rating	IP67 Rating
Rated Line Pull (Single)		9,500Lbs (4,309kgs)	12,000Lbs (5,454kgs)	15,500Lbs (7,045kgs)	17,500Lbs (7,954kgs)
Motor		6.6hp Series Wound	6.6hp Series Wound	6.6hp Series Wound	6.6hp Series Wound
Control Switch		Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead	Remote Switch, 12' (3.7m) lead
Gear Train		3-Stage Planetary	3-Stage Planetary	3-Stage Planetary	4-Stage Planetary
Gear Ratio		161.28:1	193.2:1	397:1	330:1
Clutch		Sliding Ring Gear	Sliding Ring Gear	Sliding Ring Gear	Sliding Ring Gear
Brake		Automatic In-Drum	Automatic In-Drum	Automatic In-Drum	Automatic In-Drum
Drum Size		Diameter 2.5" (63.5mm)	Diameter 2.5" (63.5mm)	Diameter 3.45"(88.0mm)	Diameter 3.7"(94.0mm)
Length		10.0" (254mm)	10.0" (254mm)	10.0" (254mm)	10.0" (254mm)
Fairlead	XRC	4-Way Roller	4-Way Roller	4-Way Roller	4-Way Roller
	XRC COMP	Competition Aluminum	Competition Aluminum	n/a	n/a
Rope	XRC	Steel	Steel	Steel	Steel
	XRC COMP	Synthetic	Synthetic	n/a	n/a
Recommended Battery		650CCA Minimum for Winching	650CCA Minimum for Winching	650CCA Minimum for Winching	650CCA Minimum for Winching
Battery Leads		22mm2, 72"(1.83m)	22mm2, 72"(1.83m)1	25mm2, 72"(1.83m)1	22mm2, 72"(1.83m)1
Finish		Textured Black	Textured Black	Textured Black	Textured Black
Weight		78.0 lbs (35.0 k)	89.0Lbs (39.0 kgs)	124.0Lbs (56.5Kgs)	141Lbs (64 kgs)
Mounting Bolt Pattern		10.0" x 4.5"	10.0" x 4.50"	10.0" x 4.50"	10.0" x 4.50" and 10.0" x 6.5"
Overall Dimensions		20.88" (L) x 6.3" (W) x 7.4" (H)	21.2" (L) x 6.4" (W) x 7.8" (H)	23.5" (L) x 8.4" (W) x 10.7" (H)	24.4" (L) x 8.4" (W) x 10.7" (H)
Cable Size		94' Length 5/16" Diameter	94' Length 3/8" Diameter	93.5' Length 25/64" Diameter	94' Length 7/16" Diameter
Mechanical Warranty		Lifetime Warranty	Lifetime Warranty	Lifetime Warranty	Lifetime Warranty
Electrical Warranty		3-Year Warranty	3-Year Warranty	3-Year Warranty	3-Year Warranty

Line Speed / AMP Draw (First Layer)

		9,500 Lb						12,000 Lb					15,500 Lb						17,500 Lb						
Line Pull	lbs	0	2000	4000	6000	8000	9500	0	3000	6000	9000	12000	0	3000	6000	9000	12000	15500	0	3000	6000	9000	12000	15500	17500
	kg	0	910	1814	2720	3625	4305	0	1360	2720	3625	5443	0	1360	2722	4080	5440	7024	0	1360	2720	4080	5440	6800	7931
Line Speed	ft/min	32.34	19.68	14.76	10.82	9.35	6.23	28.21	11.15	7.872	6.232	5.248	24.11	11.15	8.7	7.54	5.7	4.3	22.6	10.8	7.9	6.2	5.5	3.9	3.2
	m/min	9.86	6	4.5	3.3	2.85	1.9	8.6	3.4	2.4	1.9	1.6	7.35	3.4	2.65	2.3	1.74	1.4	6.9	3.3	2.4	1.9	1.6	1.2	0.99
Motor	Amps	80	165	240	320	380	435	65	163	244	315	400	70	165	240	310	375	445	75	140	210	270	330	390	435

Line Pull and Cable Capacity

		9,500 Lb				12,000 Lb				15,500 Lb				17,500 Lb			
Layers of cable		1	2	3	4	1	2	3	4	1	2	3	4	1	2	3	4
Rated line pull, Per layer	lbs	9500	8435	7640	7086	12000	10270	9200	8800	15500	12968	10992	9630	17500	14583	12411	10822
	kg	4305	3822	3460	3212	5440	4654	4169	3790	7024	5877	4982	4364	7931	6920	5625	4905
Cumulative cable	ft	16	42	72	94	16	42	72	80	20.4	46	75	92	19.68	45.92	75.44	93.48
Capacity	m	5	12	21	28	5	12	21	24	6.2	14	23	28	6	14	23	28.5

Part Numbers

	10,000 Lb	12,000 Lb	15,500 Lb	17,500 Lb
XRC Series	#97495	#97412	#97415	#97417
XRC COMP Series	#98495	#98412	n/a	n/a